

LED GROW STRIP™ - Triple Bright

Model: FA60M50-5M-24V-X-GROW (X = COLOR R:Red / B:Blue)



BENEFITS

- Nano-meter wavelength for Laboratory Growth
- View Angle 120°
- Double sided 3M Tape backing
- Ultra bright surface - mount LEDs
- Low power consumption and little heat
- No RF interference
- Long life of LEDs
- Flexible LED strip lights
- Solid-state lighting
- Continuous length
- Can be cut to size at marked intervals (Qualified personnel)
- Available in Red (660nm) and Blue (450~460nm)

APPLICATIONS

- Indoor Grow Operations
- Green Houses
- Indoor Gardening

SPECIFICATIONS

Roll Size	5 Meters (16.4 Feet)
Max Voltage	24 VDC (regulated/Class 2)
Watt Foot	4.4
Light Source	60 pcs/Meter (39.37") 5050 SMD LED
Dimensions	5000(L) x 10(W) x 2.5(H)mm (16.4' x 3/8" x 3/32")
Max Length	5 Meters (16.4 Feet)
View Angle	120°
Brightness	396~418 LM/ft (30.5cm)
Bend Radius	4 inches (100mm) Max, one flat plane
Lamp Life	>25,000 hours (average life)
IP Rating	IP22 Type A
Mount	Smooth Surface/burrows free
Operating Temperature	-25°C ~ +40°C

OPTIONAL ACCESSORIES

XLD200B-224V-FC (24VDC) One Channel Output-Class 2	CVN96L24DC (24VDC) Regulated Class 2	Wago Block Connectors (#222-413)

MODEL

FA60M50-5M-24V-X-GROW

- COLOR (R:Red, B:Blue)
- VOLTAGE (24V)
- LENGTH (5 Meters)
- LED TYPE (5050 SMD)
- LED/METER (60LED/Meter)
- COVER TYPE (Type A, no coating)
- FLEX STRIP

24V
DC Power

4.4
WATTS
FOOT

80>
CRI

flexible


VIEW ANGLE
120°

25,000+
HOURS

TRIMMABLE

DIMMABLE

UL LISTED
use only with Class 2 Type power units



DIAGRAM

